



Ahead Cell Technology Co.,Ltd

Bobbin Cell

Primary Lithium Battery

ER9V 10.8V 1.2Ah

Primary lithium-thionyl chloride
(Li-SOCl₂) Energy Type

For low drain/long term operating applications requesting superior voltage response in -55°C ~+85°C environments

Electrical characteristics

(Typical values relative to cells stored for one year or less at +30°C max.)

Nominal capacity 1.2Ah
(At 0.5mA +20°C, 6.0V cut off. The capacity restored varies according to current, temperature, cut off)

Open circuit voltage (At 20°C) 10.9V

Nominal voltage (At 0.5mA +20°C) 10.8V

Max. continuous current (at +20°C) 20mA


Typical Max. Pulse current (at +20°C) 100mA

Pulse capability: Typically up to 100mA (100mA/0.1second pulses drained every 2min at 20°C from cells with 10µA base current, yielding voltage readings above 8.0V. The readings may vary according to pulse characteristics, temperature and cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions. Consult ACT if necessary)


Storage (recommended) +30°C Max

Operating temperature range
(High and low temperature will lower the capacity and load voltage.) -55°C ~+85°C

ER9V



Typical Weight:32g



Key features

- >High and stable load voltage
- >Superior drain capacity
- >Low self-discharge rate
(less than 1% after 1 year of storage at 20°C)

Main applications

- >Radiocommunication and other military applications
- >Alarms and security systems
- >Beacons and emergency location transmitters
- >GPS equipment
- >Metering systems
- >Led lighting applications
- >Others

Storage

- >Cells should be stored in a clean & dry (less than 70% RH) area
- >Temp. should not exceed +30°C

Warning

- >Do not use if cell casing is mangled
- >Do not use different model of cell in series
- >Do not try to recharge

